

CERTIFICATE OF COMPLIANCE

Certificate Number 20190306-EX16160
Report Reference EX16160-20130418
Issue Date 2019-MARCH-06

Issued to: CDB ENGINEERING SPA
VIA MAGGI 19
26841 CASALPUSTERLENGO LODI ITALY

**This is to certify that
representative samples of** STRAINERS, PIPELINE
See addendum for models.

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: Outline of Investigation for Pipeline Strainers, Subject 321
Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190306-EX16160
Report Reference EX16160-20130418
Issue Date 2019-MARCH-06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.


Strainers, basket type, model FBC150, in the 3, 4, 6, 8 and 10 in. sizes for rated working pressure of 175 psi. Loss of head will approximate 11.19 psi for the 3 in. size at 345.6GPM, 15.17 psi for the 4 in size at 595.18GPM, 14.85 psi for the 6 in size at 1350.71GPM, 11.71 psi for the 8 in size at 2338.92GPM and 7.41 psi for the 10 in size at 3686.7GPM.

Strainers, basket type, Model(s) FBC150-Scraper, in the 3, 4, 6, and 8 in. sizes for rated working pressure of 175 psi. Loss of head will approximate 14.70 psi for the 3 in. size at 345.6 GPM, 16.63 psi for the 4 in size at 595.18 GPM, 10.84 psi for the 6 in size at 1350.71 GPM, and 8.50 psi for the 8 in size at 2338.92 GPM

Strainers, Y-type, Model FYF-800, in the 2 in. size for a Rated working pressure of 175 psi. Loss of head will approximate 21.90 psi for the 2 in. size at 156.9 GPM.

Strainers, Y-type, Model FYC-150, in the 2.5, 3, 4, 6, 8, and 10 in. sizes. Loss of head will approximate 5.55 psi for the 2.5 in. size at 223.8 GPM, 7.89 psi for the 3 in. size at 345.6 GPM, 6.84 psi for the 4 in. size at 595.2 GPM, 7.60 psi for the 6 in. size at 1350.7 GPM, 7.57 for the 8 in. size at 2338.9 GPM, and 5.44 psi for the 10 in. size at 3686.7 GPM.

Strainers, basket type, Model FTX2V-150, in the 4 inch size for a Rated working pressure of 175 psi. Loss of head will approximate 3.82 psi for the 4 in. size at 595.2 GPM.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

